

Ultra Rim Clamp



Jackbar Setting Gauge

FEATURES AND BENEFITS

- From sizes 4"—72"+
- Align and reform X65, X70, and X80 pipe with wall thicknesses up to 1 3/8"
- Capable of reforming pipe with an out-of-round condition of up to 2"
- Galvanized jackscrews with pivoting pads for precise reforming pressure
- Pivot points are made from stainless steel so one clamp will work for all applications
- Heavy duty latching mechanism for stability and safety
- Hinged flip-up jackbars allow for simple pipe mating and allow for full 360° welding
- Jackscrew Setting Gauge makes initial setup easy
- Torque wrench supplied for accurate reforming pressure



Model 258U



OVERVIEW

The Sawyer Ultra Rim Clamp offers more extreme reclaiming capabilities. The Ultra aligns and reforms X65, X70, and X80 pipe with wall thicknesses up to 1 3/8" and is capable of reforming pipe with an out-of-round condition of up to 2". Multiple jackscrews apply precise reforming pressure. The clamp can be used for all applications without contamination and comes with a Jackscrew Setting Gauge which saves considerable time and effort in trying to balance the clamp once it's in position.

ESTIMATED SHIPPING WEIGHT

Model No.	Description	Weight
258U-0406	Ultra Rim Clamp, 4"-6"	Call for dimensions
258U-0608	Ultra Rim Clamp, 6"-8"	Call for dimensions
258U-0810	Ultra Rim Clamp, 8"-10"	Call for dimensions
258U-1012	Ultra Rim Clamp, 10"-12"	310 lbs. 140.61 kg.
258U-1420	Ultra Rim Clamp, 14"-20"	440 lbs. 149.69 kg.
258U-1824	Ultra Rim Clamp, 18"-24"	462 lbs. 209.56 kg.
258U-2026	Ultra Rim Clamp, 20"-26"	480 lbs. 217.72 kg.
258U-2228	Ultra Rim Clamp, 22"-28"	495 lbs. 224.52 kg.
258U-3036	Ultra Rim Clamp, 30"-36"	555 lbs. 251.74 kg.
258U-3440	Ultra Rim Clamp, 34"-40"	590 lbs. 267.62 kg.
258U-4450	Ultra Rim Clamp, 44"-50"	882 lbs. 400.07 kg.
258U-5056	Ultra Rim Clamp, 50"-56"	950 lbs. 430.91 kg.
258U-6672	Ultra Rim Clamp, 66"-72"	1060 lbs. 480.80 kg.

Follow us on social media and watch product videos on our YouTube channel **Sawyer Mfg**

918-834-2550



sawyer^{mfg}.com