

15 Ton Strap Bender



Model 273-15



OVERVIEW

The 15 Ton Strap Bender is capable of performing face, root or side bend tests. Designed for destructive weld testing and can be operated vertically or horizontally. With improved plating and powder coating for corrosion resistance, this equipment will safely perform guided bend testing for years to come.

FEATURES AND BENEFITS

- For weld coupon testing
- Comes standard with ASME 3/8" die and plunger, optional sets available to meet code
- For field and shop applications
- Horizontal or vertical use
- Optional accessories: Electric or Pneumatic Pump
- 1 year warranty

ESTIMATED SHIPPING WEIGHT

Model No.	Description	Weight
273-15	15T Strap Bender w/Hand Pump	200 lbs. 90.7 kg.
273-15E	15T Strap Bender w/Electric Pump	250 lbs. 113.4 kg.
273-15A	15T Strap Bender w/Pneumatic Pump	250 lbs. 113.4 kg.
4FF-7ASME	ASME Die/Plunger Set	Call for Weight
SPECIAL	API Die/Plunger Set	Call for Weight
13R-15	Carrying Case	Call for Weight

Follow us on social media and watch product videos on our YouTube channel [Sawyer Mfg](#)

918-834-2550



sawyeremfg.com

ACCESSORIES

HAND PUMP (526-5)

- Formed handle provides less flex
- Durable all metal construction for long life
- Fill cap seal acts as safety valve preventing over pressurizing



FOOT PUMP (526-20)

- Compact, lightweight, and portable
- Air requirement, operates at 40-100 psi (3-8 bar) at the pump
- Permanently vented reservoir cap with an internal relief valve



ELECTRIC PUMP (526-28)

- Operating pressures to 10,000 psi (700 bar)
- 1/2 hp, 3,450 rpm, single-phase, thermal protected induction motor; 10 ft. remote control cord
- Extremely quiet noise level



DIE & PLUNGER SETS

*ASME 3/4" also available



ASME 1/4"

ASME 3/8"

ASME 1/2"

API 1104